

Straight panel plug 75x75 2P+E 32A IP44/54 SpeedPRO



32 A

230 V

2P+T

IP44/54

6h

IK08

TECHNICAL DATA

IEC-Amperage	32 A
Voltage	200-250 V
Poles	2P+T
Protection degree	IP44/54
Hour position	6h
Impact resistance	IK08
Colour	Blue
Connection system	Screw connection
Material	ABS+PA6
Contact material	Nickel-plated brass
Wire flexible	2,5-6 mm ²
Net weight (kg)	0.131
ETIM 9.0	EC001319
Ball pressure test	125°C housings active parts / 70°C other parts
Insulating resistance	>10 MΩ @ 500 Vdc
Dielectric strength	2.5 kV
Operating temperature	-25°C / 40°C
Temperature resistance	-25°C / 70°C

LOGISTICS

Minimum sales unit 1

EAN unit



8429760273233

Quantity inner box 5

EAN inner box



8429760283232

Quantity master box 60

EAN master box



8429760293231

HS code 85366990

STANDARDS AND CERTIFICATIONS

Applied standards	IEC/EN 60309-1, IEC/EN 60309-2
Low Voltage Directive	Low Voltage Directive 2014/35/UE
RoHS Directive	RoHS 2011/65/UE and modifications