

Schuko panel socket 2P+TTL 16A IP54 SpeedPRO



16 A

250V

2P+T

IP54

6h

IK07

TECHNICAL DATA

IEC-Amperage	16 A
Voltage	250 V
Poles	2P+T
Protection degree	IP54
Hour position	6h
Impact resistance	IK07
Colour	Blue
Connection system	Screw connection
Material	ABS+PA6
Contact material	Nickel-plated brass
Wire flexible	1-2,5 mm ²
Net weight (kg)	0.044
ETIM 9.0	EC001325
Ball pressure test	125°C housings active parts / 70°C other parts
Insulating resistance	5 MΩ @ 500 Vdc
Dielectric strength	2.5 kV
Operating temperature	-25°C / 40°C
Temperature resistance	-25°C / 70°C

LOGISTICS

Minimum sales unit	1
EAN unit	 8429760441267
Quantity inner box	30
EAN inner box	 8429760741266
Quantity master box	180
EAN master box	 8429760741268
HS code	85366990

STANDARDS AND CERTIFICATIONS

Applied standards	UNE 20315-1-1, UNE 20315-1-2 (IEC 60884-1)
Low Voltage Directive	Low Voltage Directive 2014/35/UE
RoHS Directive	RoHS 2011/65/UE and modifications