

Triple Schuko rubber adapter, 5P power strip IP54



16 A

400V

5P

IP54

IK08

TECHNICAL DATA

IEC-Amperage	16 A
Voltage	400 V
Poles	5P
Protection degree	IP54
Impact resistance	IK08
Colour	Black
Connection system	Screw connection
Material	Rubber
Contact material	Brass (nickel-plated grounding contact)
Wire flexible	1-2,5 mm ²
Net weight (kg)	0.358
ETIM 9.0	EC000330
Ball pressure test	125°C housings active parts / 70°C other parts
Insulating resistance	5 MΩ @ 500 Vdc
Dielectric strength	4 kV
Operating temperature	-5°C / 40°C
Temperature resistance	-25°C / 70°C

LOGISTICS

Minimum sales unit	1
EAN unit	 8429760823056
Quantity inner box	5
EAN inner box	 18429760823053
Quantity master box	15
EAN master box	 28429760823050
HS code	85366990

STANDARDS AND CERTIFICATIONS

Applied standards	UNE 20315-1-1, UNE 20315-1-2, UNE 20315-2-5 (IEC 60884-1)
Low Voltage Directive	Low Voltage Directive 2014/35/UE
RoHS Directive	RoHS 2011/65/UE and modifications