

French rubber socket 2P+TTL 16A IP44 SpeedPRO



16 A

250V

2P+TTL

IP44

IK08

TECHNICAL DATA

IEC-Amperage	16 A
Voltage	250 V
Poles	2P+TTL
Protection degree	IP44
Impact resistance	IK08
Colour	Black
Connection system	Screw connection
Material	Rubber
Contact material	Brass (nickel-plated grounding contact)
Wire flexible	1-2,5 mm ²
Net weight (kg)	0.148
ETIM 9.0	EC001327
Ball pressure test	125°C housings active parts / 70°C other parts
Insulating resistance	5 MΩ @ 500 Vdc
Dielectric strength	2 kV
Operating temperature	-5°C / 40°C
Temperature resistance	-25°C / 70°C

LOGISTICS

Minimum sales unit	1
EAN unit	 8429760244523
Quantity inner box	10
EAN inner box	 8429760254522
Quantity master box	60
EAN master box	 8429760264521
HS code	85366990

STANDARDS AND CERTIFICATIONS

Applied standards	UNE 20315-1-1 / UNE 20315-1-2 (IEC 60884-1 + CEE 7)
Low Voltage Directive	Low Voltage Directive 2014/35/UE
RoHS Directive	RoHS 2011/65/UE and modifications