

Mobile French socket 16A IP54 SpeedPRO



16 A

250V

2P+T

IP54

IK08

TECHNICAL DATA

IEC-Amperage	16 A
Voltage	250 V
Poles	2P+T
Protection degree	IP54
Impact resistance	IK08
Colour	Black
Connection system	Screw connection
Material	Rubber
Contact material	Brass (nickel-plated grounding contact)
Wire flexible	1-2,5 mm ²
Net weight (kg)	0.095
ETIM 9.0	EC001327
Ball pressure test	125°C housings active parts / 70°C other parts
Insulating resistance	5 MΩ @ 500 Vdc
Dielectric strength	4 kV
Operating temperature	-5°C / 40°C
Temperature resistance	-25°C / 70°C

LOGISTICS

Minimum sales unit	1
--------------------	---

EAN unit



8429760821502

Quantity inner box	6
--------------------	---

EAN inner box



18429760821509

Quantity master box	180
---------------------	-----

EAN master box



28429760821506

HS code	85366990
---------	----------

STANDARDS AND CERTIFICATIONS

Applied standards	NF C 61-314 (IEC 60884-1)
Low Voltage Directive	Low Voltage Directive 2014/35/UE
RoHS Directive	RoHS 2011/65/UE and modifications