


Angled panel socket 10° 3P+T 32A IP44/54 SpeedPRO



32 A

400 V

3P+T

IP44/54

6h

IK08

TECHNICAL DATA

IEC-Amperage	32 A
Voltage	380-415 V
Poles	3P+T
Protection degree	IP44/54
Hour position	6h
Impact resistance	IK08
Colour	Red
Connection system	Screw connection
Material	ABS+PA6
Contact material	Brass
Wire flexible	2,5-6 mm ²
Net weight (kg)	0.195
ETIM 9.0	EC001317
Ball pressure test	125°C housings active parts / 70°C other parts
Insulating resistance	>10 MΩ @ 500 Vdc
Dielectric strength	2.5 kV
Operating temperature	-25°C / 40°C
Temperature resistance	-25°C / 70°C

LOGISTICS

Minimum sales unit	1
EAN unit	 8429760216438
Quantity inner box	5
EAN inner box	 8429760226437
Quantity master box	60
EAN master box	 8429760236436
HS code	85366990

STANDARDS AND CERTIFICATIONS

Applied standards	IEC/EN 60309-1, IEC/EN 60309-2
Low Voltage Directive	Low Voltage Directive 2014/35/UE
RoHS Directive	RoHS 2011/65/UE and modifications