

Angled panel socket 10° 2P+E 16A IP67 SpeedPRO



16 A

230 V

2P+T

IP67

6h

IK08

TECHNICAL DATA

|                        |                                                |
|------------------------|------------------------------------------------|
| IEC-Amperage           | 16 A                                           |
| Voltage                | 200-250 V                                      |
| Poles                  | 2P+T                                           |
| Protection degree      | IP67                                           |
| Hour position          | 6h                                             |
| Impact resistance      | IK08                                           |
| Colour                 | Blue                                           |
| Connection system      | Screw connection                               |
| Material               | ABS+PA6                                        |
| Contact material       | Brass                                          |
| Wire flexible          | 1-2,5 mm <sup>2</sup>                          |
| Net weight (kg)        | 0.138                                          |
| ETIM 9.0               | EC001317                                       |
| Ball pressure test     | 125°C housings active parts / 70°C other parts |
| Insulating resistance  | >10 MΩ @ 500 Vdc                               |
| Dielectric strength    | 2.5 kV                                         |
| Operating temperature  | -25°C / 40°C                                   |
| Temperature resistance | -25°C / 70°C                                   |

LOGISTICS

|                     |                                                                                                       |
|---------------------|-------------------------------------------------------------------------------------------------------|
| Minimum sales unit  | 1                                                                                                     |
| EAN unit            | <br>8429760216551   |
| Quantity inner box  | 10                                                                                                    |
| EAN inner box       | <br>8429760226550 |
| Quantity master box | 120                                                                                                   |
| EAN master box      | <br>8429760236559 |
| HS code             | 85366990                                                                                              |

STANDARDS AND CERTIFICATIONS

|                       |                                   |
|-----------------------|-----------------------------------|
| Applied standards     | IEC/EN 60309-1, IEC/EN 60309-2    |
| Low Voltage Directive | Low Voltage Directive 2014/35/UE  |
| RoHS Directive        | RoHS 2011/65/UE and modifications |