

Wall-mounted socket 2P+E 16A IP66/67 SpeedPRO



16 A

230 V

2P+T

IP66/67

6h

IK08

TECHNICAL DATA

IEC-Amperage	16 A
Voltage	200-250 V
Poles	2P+T
Protection degree	IP66/67
Hour position	6h
Impact resistance	IK08
Colour	Blue
Connection system	Screw connection
Material	ABS+PA6
Contact material	Brass
Wire flexible	1-2,5 mm ²
Net weight (kg)	0.278
ETIM 9.0	EC001321
Ball pressure test	125°C housings active parts / 70°C other parts
Insulating resistance	>10 MΩ @ 500 Vdc
Dielectric strength	2.5 kV
Operating temperature	-25°C / 40°C
Temperature resistance	-25°C / 70°C

LOGISTICS

Minimum sales unit 1

EAN unit



8429760217695

Quantity inner box 3

EAN inner box



8429760227694

Quantity master box 36

EAN master box



8429760237693

HS code 85366990

STANDARDS AND CERTIFICATIONS

Applied standards	IEC/EN 60309-1, IEC/EN 60309-2
Low Voltage Directive	Low Voltage Directive 2014/35/UE
RoHS Directive	RoHS 2011/65/UE and modifications