

Wall-mounted angled socket 90° 3P+N+E 32A IP67 SpeedPRO



32 A

400 V

3P+N+T

IP67

6h

IK08

TECHNICAL DATA

IEC-Amperage	32 A
Voltage	200/346-240/415 V
Poles	3P+N+T
Protection degree	IP67
Hour position	6h
Impact resistance	IK08
Colour	Red
Connection system	Screw connection
Material	ABS+PA6
Contact material	Brass
Wire flexible	2,5-6 mm ²
Net weight (kg)	0.332
ETIM 9.0	EC001321
Ball pressure test	125°C housings active parts / 70°C other parts
Insulating resistance	>10 MΩ @ 500 Vdc
Dielectric strength	2.5 kV
Operating temperature	-25°C / 40°C
Temperature resistance	-25°C / 70°C

LOGISTICS

Minimum sales unit 1

EAN unit



8429760216230

Quantity inner box 2

EAN inner box



8429760226239

Quantity master box 24

EAN master box



8429760236238

HS code 85366990

STANDARDS AND CERTIFICATIONS

Applied standards	IEC/EN 60309-1, IEC/EN 60309-2
Low Voltage Directive	Low Voltage Directive 2014/35/UE
RoHS Directive	RoHS 2011/65/UE and modifications