

## Wall-mounted socket 3P+N+E 32A IP66/67 SpeedPRO



32 A

400 V

3P+N+T

IP66/67

6h

IK08

## TECHNICAL DATA

|                        |                                                |
|------------------------|------------------------------------------------|
| IEC-Amperage           | 32 A                                           |
| Voltage                | 200/346-240/415 V                              |
| Poles                  | 3P+N+T                                         |
| Protection degree      | IP66/67                                        |
| Hour position          | 6h                                             |
| Impact resistance      | IK08                                           |
| Colour                 | Red                                            |
| Connection system      | Screw connection                               |
| Material               | ABS+PA6                                        |
| Contact material       | Brass                                          |
| Wire flexible          | 2,5-6 mm <sup>2</sup>                          |
| Net weight (kg)        | 0.396                                          |
| ETIM 9.0               | EC001321                                       |
| Ball pressure test     | 125°C housings active parts / 70°C other parts |
| Insulating resistance  | >10 MΩ @ 500 Vdc                               |
| Dielectric strength    | 2.5 kV                                         |
| Operating temperature  | -25°C / 40°C                                   |
| Temperature resistance | -25°C / 70°C                                   |

## LOGISTICS

|                     |                                                                                                       |
|---------------------|-------------------------------------------------------------------------------------------------------|
| Minimum sales unit  | 1                                                                                                     |
| EAN unit            | <br>8429760217763   |
| Quantity inner box  | 2                                                                                                     |
| EAN inner box       | <br>8429760227762 |
| Quantity master box | 24                                                                                                    |
| EAN master box      | <br>8429760237761 |
| HS code             | 85366990                                                                                              |

## STANDARDS AND CERTIFICATIONS

|                       |                                   |
|-----------------------|-----------------------------------|
| Applied standards     | IEC/EN 60309-1, IEC/EN 60309-2    |
| Low Voltage Directive | Low Voltage Directive 2014/35/UE  |
| RoHS Directive        | RoHS 2011/65/UE and modifications |