

6-module IP65 knockout enclosure for 1 mechanism AcquaCOMBI, 305x125x107 mm



6M

IP65

IK08

305x125x107 mm

TECHNICAL DATA

Modules	6
ETIM 9.0	EC000214
Linkable	No
Installation	Surface
Compatible with DIN rail	Yes
Net weight (kg)	0.602
Door	Transparent
Use	Indoor-Outdoor
Built-in components	35 mm DIN rail – screw plugs
Optional accessories	SPTC-4/3911
Dielectric strength	3.75
Impulse withstand voltage (kV)	4
Insulation class	Class II
Short-circuit current (kA)	10
Thermal power dissipation capacity (W)	14
IP Protection Degree	IP65
Impact resistance	IK08
Material	ABS + PC door
Colour	Grey
Glow wire test	650°C
Ball pressure test	70°C
Halogen-free materials	Yes
UV Resistance	Yes
Operating temperature range (°C)	-25°C / 40°C
Transport and storage temperature	-25°C / 70°C
Overall height (mm)	305
Overall width (mm)	125
Overall depth (mm)	107
Internal height (mm)	295
Internal width (mm)	115
Internal depth (mm)	70

LOGISTICS

Minimum sales unit	1
EAN unit	
	8429760277279
Quantity master box	18
EAN master box	
	8429760297277
HS Code	85381000

STANDARDS AND CERTIFICATIONS

Applied standards	IEC 62208, IEC 61439-1, IEC 61439-3 (Applicable clauses)
Low Voltage Directive	Low Voltage Directive 2014/35/UE
Low voltage electrotechnical regulations	REBT 2002