

## 6-module IP65 blank enclosure AcquaCOMBI, 490x125x107 mm



6M

IP65

IK08

490x125x107 mm

## TECHNICAL DATA

|                                        |                              |
|----------------------------------------|------------------------------|
| Modules                                | 6                            |
| ETIM 9.0                               | EC000214                     |
| Linkable                               | No                           |
| Installation                           | Surface                      |
| Compatible with DIN rail               | Yes                          |
| Net weight (kg)                        | 0.912                        |
| Door                                   | Transparent                  |
| Use                                    | Indoor-Outdoor               |
| Built-in components                    | 35 mm DIN rail – screw plugs |
| Optional accessories                   | SPTC-4/3911                  |
| Dielectric strength                    | 3.75                         |
| Impulse withstand voltage (kV)         | 4                            |
| Insulation class                       | Class II                     |
| Short-circuit current (kA)             | 10                           |
| Thermal power dissipation capacity (W) | 20                           |
| IP Protection Degree                   | IP65                         |
| Impact resistance                      | IK08                         |
| Material                               | ABS + PC door                |
| Colour                                 | Grey                         |
| Glow wire test                         | 650°C                        |
| Ball pressure test                     | 70°C                         |
| Halogen-free materials                 | Yes                          |
| UV Resistance                          | Yes                          |
| Operating temperature range (°C)       | -25°C / 40°C                 |
| Transport and storage temperature      | -25°C / 70°C                 |
| Overall height (mm)                    | 490                          |
| Overall width (mm)                     | 125                          |
| Overall depth (mm)                     | 107                          |
| Internal height (mm)                   | 480                          |
| Internal width (mm)                    | 115                          |
| Internal depth (mm)                    | 70                           |

## LOGISTICS

|                     |                                                                                      |
|---------------------|--------------------------------------------------------------------------------------|
| Minimum sales unit  | 1                                                                                    |
| EAN unit            |    |
|                     | 8429760229308                                                                        |
| Quantity master box | 12                                                                                   |
| EAN master box      |  |
|                     | 8429760239307                                                                        |
| HS Code             | 85381000                                                                             |

## STANDARDS AND CERTIFICATIONS

|                                          |                                                          |
|------------------------------------------|----------------------------------------------------------|
| Applied standards                        | IEC 62208, IEC 61439-1, IEC 61439-3 (Applicable clauses) |
| Low Voltage Directive                    | Low Voltage Directive 2014/35/UE                         |
| Low voltage electrotechnical regulations | REBT 2002                                                |