

9-module IP65 blank enclosure AcquaCOMBI, 350x215x150 mm



9M

IP65

IK08

350x215x150 mm

TECHNICAL DATA

Modules	9
ETIM 9.0	EC000214
Linkable	No
Installation	Surface
Compatible with DIN rail	Yes
Net weight (kg)	1.062
Door	Transparent
Use	Indoor-Outdoor
Built-in components	35 mm DIN rail – screw plugs
Optional accessories	SPTC-4/SPTA-12/RG-12/3911/3917/150039570
Dielectric strength	3.75
Impulse withstand voltage (kV)	4
Insulation class	Class II
Short-circuit current (kA)	10
Thermal power dissipation capacity (W)	23
IP Protection Degree	IP65
Impact resistance	IK08
Material	ABS + PC door
Colour	Grey
Glow wire test	650°C
Ball pressure test	70°C
Halogen-free materials	Yes
UV Resistance	Yes
Operating temperature range (°C)	-25°C / 40°C
Transport and storage temperature	-25°C / 70°C
Overall height (mm)	350
Overall width (mm)	215
Overall depth (mm)	150
Internal height (mm)	340
Internal width (mm)	205
Internal depth (mm)	100

LOGISTICS

Minimum sales unit	1
EAN unit	
	8429760229322
Quantity master box	6
EAN master box	
	8429760239321
HS Code	85381000

STANDARDS AND CERTIFICATIONS

Applied standards	IEC 62208, IEC 61439-1, IEC 61439-3 (Applicable clauses)
Low Voltage Directive	Low Voltage Directive 2014/35/UE
Low voltage electrotechnical regulations	REBT 2002