

12-module IP65 blank enclosure AcquaCOMBI, 400x265x150 mm



12M

IP65

IK08

400x265x150 mm

TECHNICAL DATA

Modules	12
ETIM 9.0	EC000214
Linkable	No
Installation	Surface
Compatible with DIN rail	Yes
Net weight (kg)	1.358
Door	Transparent
Use	Indoor-Outdoor
Built-in components	35 mm DIN rail – screw plugs
Optional accessories	SPTC-4/SPTA-12/RG-12/3911/3917
Dielectric strength	3.75
Impulse withstand voltage (kV)	4
Insulation class	Class II
Short-circuit current (kA)	10
Thermal power dissipation capacity (W)	31
IP Protection Degree	IP65
Impact resistance	IK08
Material	ABS + PC door
Colour	Grey
Glow wire test	650°C
Ball pressure test	70°C
Halogen-free materials	Yes
UV Resistance	Yes
Operating temperature range (°C)	-25°C / 40°C
Transport and storage temperature	-25°C / 70°C
Overall height (mm)	400
Overall width (mm)	265
Overall depth (mm)	153
Internal height (mm)	390
Internal width (mm)	255
Internal depth (mm)	95

LOGISTICS

Minimum sales unit	1
EAN unit	
	8429760246602
Quantity master box	4
EAN master box	
	8429760266600
HS Code	85381000

STANDARDS AND CERTIFICATIONS

Applied standards	IEC 62208, IEC 61439-1, IEC 61439-3 (Applicable clauses)
Low Voltage Directive	Low Voltage Directive 2014/35/UE
Low voltage electrotechnical regulations	REBT 2002