

13-module IP65 blank enclosure AcquaCOMBI, 175x330x155 mm



13M

IP65

IK08

175x330x155 mm

TECHNICAL DATA

Modules	13
ETIM 9.0	EC000214
Linkable	Yes
Installation	Surface
Compatible with DIN rail	Yes
Net weight (kg)	1.41
Door	Transparent
Use	Indoor-Outdoor
Built-in components	35 mm DIN rail – screw plugs
Optional accessories	3911/3917/3900/3903/3910/SPTC-4/SPTA-12/RG-12
Dielectric strength	3.75
Impulse withstand voltage (kV)	4
Insulation class	Class II
Short-circuit current (kA)	10
Thermal power dissipation capacity (W)	24
IP Protection Degree	IP65
Impact resistance	IK08
Material	ABS + PC door
Colour	Grey
Glow wire test	650°C
Ball pressure test	70°C
Halogen-free materials	Yes
UV Resistance	Yes
Operating temperature range (°C)	-25°C / 40°C
Transport and storage temperature	-25°C / 70°C
Overall height (mm)	175
Overall width (mm)	330
Overall depth (mm)	155
Internal height (mm)	165
Internal width (mm)	320
Internal depth (mm)	105

LOGISTICS

Minimum sales unit 1

EAN unit



8429760222347

Quantity master box 6

EAN master box



8429760232346

HS Code 85381000

STANDARDS AND CERTIFICATIONS

Applied standards	IEC 62208, IEC 61439-1, IEC 61439-3 (Applicable clauses)
Low Voltage Directive	Low Voltage Directive 2014/35/UE
Low voltage electrotechnical regulations	REBT 2002